

Product Specification Sheet

100P[™] Industrial Paint Marker



SPECIFICATIONS

- Item # : 10201 Black
 - 10202 Blue 10203 Green 10204 Red 10205 White 10206 Yellow 10207 Orange

10209 Bright Green 10210 Silver 10211 Pink 10212 Violet 10213 Light Blue 10214 Gold 10215 Brown 10100 HD Bullet Tip

- Style: Valve Activated
- Tip Type: Bullet
- Marking Widths: 2 mm. (0.078")
- Dimensions: 5.69" L x 0.56" Ø (144 x 14 mm.) *
- Marking Temp. Range: -50° to 150° Fahrenheit (-45° to 65° C)
- Dry Time: approx. 45 sec.
- Quantity/ Weight Per Box: 12ea./ 0.75 lb./ (340 g.)
- Quantity/ Weight Per Case: 144ea./ 9 lb./ (4.1 kg.)
- **Directions For Use:** Shake vigorously with cap on. Press tip until inked. Replace cap after use.
- * Dimensions taken w/ marker capped.

PRODUCT FEATURES

- Two available sizes for medium and fine line marking.
- Heavy duty aluminum barrel and air-tight cap withstand industrial use.
- Liquid paint is dispensed by a patented valve to ensure smooth paint flow.
- Paint is UV and weather resistant.
- Marker fits in U-Holder™

TYPICAL USES

• Marks well on rusty and oily metals, dry or damp wood, glass, plastics, rubber tape, cardboard, waxed cartons, ceramics, tiles, concrete, and more.

SAFETY INFORMATION

- Read MSDS before using (available online at www.umarkers.com).
- Keep out of reach of children. For professional use only.



U-Mark, Inc. • 102 Iowa Ave., Belleville, IL 62220 USA • tel. 618-235-7500 • fax 425-962-9840 • www.umarkers.com



